

DRACMA

DRC002



INDOOR Recessed Panel



Description

DRACMA - DRACMA LED PANEL 600x600 40W - 3000K - SQUARE OPAL DIFFUSOR

600x600mm or 300x1200mm LED panel with white painted aluminium frame and polystyrene microprismatic diffuser (for the UGR<19 version). Plastic frame for STANDARD version. High efficiency luminaire, flicker free. Available in two gradations (3000K and 4000K), with UGR<19 (for VDU workstations), with CRI>90 (for public offices and retail sector) as on/off version, 0-10V push dimm and DALI versions with remote LED driver included. Suitable for recessed mounting on modular false ceilings with exposed structure (600x600mm), and recessed on plasterboard surfaces, suspended and ceiling mounting with related accessories to be ordered separately (except STANDARD version). Emergency kit available (3 hours) to be ordered separately.



Product features

Etim group:	EG000027
Etim class:	EC002892
Material:	Aluminium
Colour:	White
Dimensions:	595 x 595 x 10 mm
Net weight:	3.8 kg
Lamp holder:	OTHER
Source:	LED
Power:	40W
Gradations:	3000K
Light emission:	Direct
Nominal direct light beam:	4190 lm
Beam angle:	120°
CRI:	>80
Ugr:	<19
Power supply :	220-240V
Life time:	50000h
Macadam:	SDMC3
Protection degree:	IP40
Insulation class:	II

In order to ensure a constant updating of its products, ROSSINI ILLUMINAZIONE reserves the right to make changes to improve without notice.

DRACMA

DRC002

