

YEN

YEN108NDA


INDOOR Linear system



Description

LED FITTING 24+12W 4000K DALI - YEN

LED linear luminaire, for direct or direct/indirect light emission, with on board or remote driver, for ceiling installation (with ceiling kit), suspended (with suspension kit and ceiling rose), or in-line configurations (with angle or linear joints, up to 1500W). Highly versatile thanks to the many possible combinations given by the different modules that can be installed, the three-phase track, the opal or anti-glare optic for UGR<19 particularly suitable for VDU workstations. Minimalistic-designed luminaire with a square-shaped and linear extruded aluminium body, available in single or double versions, painted with epoxy powders in three finishes (white, black and grey). Available in different sizes and related powers, in two gradations (3000K and 4000K) and, in some versions, with DALI protocol on request. As accessories to be ordered separately: end caps kit, diffusers and other accessories.



Product features

Etim group:	EG000027
Etim class:	EC001743
Installation:	Linear system
Material:	Aluminium
Colour:	Black
Dimensions:	1080 x 46 x 92 mm
Net weight:	3.2 kg
Lamp holder:	OTHER
Source:	LED
Power:	24W+12W
Gradations:	4000K
Light emission:	Direct/Indirect
Nominal direct light beam:	3573 lm
Nominal indirect light beam:	1787 lm
Beam angle:	120°
CRI:	>90
Dimmer:	DALI
Power supply :	220-240V
Life time:	50000h
Macadam:	SDMC3
Protection degree:	IP20
Resistance to fracture:	IK05
Insulation class:	I

Note: End caps, diffuser, fixing kit, ceiling rose and joints to be ordered separately. On request the product can be customized in direct-indirect version, special finishes, sizes and CCT.

In order to ensure a constant updating of its products, ROSSINI ILLUMINAZIONE reserves the right to make changes to improve without notice.

YEN

YEN108NDA

