# NASHI EVO NAE006BDA

INDOOR DIFFUSER DIRECT IN-LINE MOUNTING






## Description

#### NASHI EVO - LED MONO IL 33W 4K MP W DALI - START I INF

LED luminaire for direct or direct/indirect lightemission for ceiling or suspende installation. Made in Italy extruded aluminium body, polycarbonateoptics and diffusers with high efficiency latest generation LED moduls. In-line or angle configuration with different installation solutions and light beams. The quick connection of the LED source by magnet and the safety cable supplied, offer easyand safe replacement in case of maintenance. Available with microprismatic diffuser and optic with lens UGR<19. Two finishes (white and black), two gradation (3000K and 4000K). On board driver.





### Product features

Source:

Etim group: EG000027
Etim class: EC001743

Installation: Linear system

Material: Aluminium

Colour: White

Dimensions: 1700 x 65 x 75 mm

LED

Net weight: 2.5 kg
Lamp holder: OTHER

, p

Power: 33W

Gradations: 4000K

Light emission: Direct

Real direct light beam: 4023 lm

Efficiency: 123lm/W

CRI: >90

Photobiological risk: RG0

Dimmer: DALI2

Power supply: 220-240V

Life time: 50000h

Protection degree: IP20

Insulation class:

Warranty: 5

Note: Customizable in special finishes, double ignition, optics, sizes, luminous fluxes, versions with special outside lines, motion, twilight and emergency sensor with 1-3 hours battery life.

In order to ensure a constant updating of its products, ROSSINI ILLUMINAZIONE reserves the right to make changes to improve without notice.

# NASHI EVO NAE006BDA







