NASHI EVO NAE023NDA

INDOOR OPTIC DIRECT IN-LINE MOUNTING






Description

LED MONO IN 37W 3K LENS 60° B DAL - NASHI EVO

LED luminaire for direct or direct/indirect lightemission for ceiling or suspende installation. Made in Italy extruded aluminium body, polycarbonateoptics and diffusers with high efficiency latest generation LED moduls. In-line or angle configuration with different installation solutions and light beams. The quick connection of the LED source by magnet and the safety cable supplied, offer easyand safe replacement in case of maintenance. Available with microprismatic diffuser and optic with lens UGR<19. Two finishes (white and black), two gradation (3000K and 4000K). On board driver.






Product features	
Etim group:	EG000027
Etim class:	EC001743
Installation:	Linear system
Material:	Aluminium
Colour:	Black
Dimensions:	1690 x 65 x 75 mm
Net weight:	2.5 kg
Lamp holder:	OTHER
Source:	LED
Power:	37W
Gradations:	3000K
Light emission:	Direct
Real direct light beam:	4694 lm
Efficiency:	127lm/W
Beam angle:	60°
CRI:	>90
Photobiological risk:	RG0
Ugr:	<19
Dimmer:	DALI2
Power supply :	220-240V
Life time:	50000h
Protection degree:	IP20
Insulation class:	I
Warranty:	5

Note: Customizable in special finishes, double ignition, optics, sizes, luminous fluxes, versions with special outside lines, motion, twilight and emergency sensor with 1-3 hours battery life.

In order to ensure a constant updating of its products, ROSSINI ILLUMINAZIONE reserves the right to make changes to improve without notice.



NASHI EVO NAE023NDA



Rossiniilluminazione.