

SMART SMA103



INDOOR Ceiling recessed



Description

RECESSED LED 22W 3K - SMART

Round LED downlight, with die-cast aluminium body and transparent glass diffuser. Integrated COB LED and remote driver On-Off included. 0-10V dimmable and DALI version on request. Thanks to the different diameters it is suitable to replace the traditional fluorescent downlights (2x13W, 2x18W, 2x36W). Thanks to its backward optics it gives a uniform and neat light emission (light beam angle at 40°- 45°), reducing the glare effect and achieving UGR<19, for VDU workstations. CRI>90: for retail installation. Available in white finish, in different sizes and related powers and in two gradations (3000K and 4000K). Emergency kit 3H to be ordered separately.



Product features

Etim group:	EG000027
Etim class:	EC001744
Installation:	Ceiling recessed
Material:	Aluminium
Colour:	White
Dimensions:	Ø 175 x 100 mm
Hole:	155mm
Lamp holder:	OTHER
Source:	LED
Power:	22W
Gradations:	3000K
Light emission:	Direct
Real direct light beam:	1860 lm
Efficiency:	85lm/W
Beam angle:	40°
CRI:	>90
Photobiological risk:	RG0
Ugr:	<19
Power supply :	220-240V
Life time:	50000h
Protection degree:	IP20
Resistance to fracture:	IK03
Insulation class:	II
Warranty:	2

In order to ensure a constant updating of its products, ROSSINI ILLUMINAZIONE reserves the right to make changes to improve without notice.

SMART SMA103

