MAAR MAA101NDA


Track and floodlight




Description

MAAR - - THREEPHASE MINI

High efficiency track-mounted LED pojector adjustable on two axes. Die-cast aluminium, powder coated. It can be mounted on threephase track GROOVE evo, YEN BINARIO and on monophase track SQUASH and SQUASH PRO. Light beam lens 36°, other lenses (to be ordered separately) to adjusted the light beam at 12°, 24° and 60°. Thanks to its excellent colour rendering (CRI?90) it is also suitable for shops and retail aeas. Provides a uniform light emission without glare and shadows. Available in different powers, in three finishes (white, black and grey) and two gradations (3000K and 4000K). Availablewall adapter as accessory (to be ordered separately).





Product features	
Etim group:	EG000027
Etim class:	EC001744
Dimensions:	Ø 55 x 140 x 223 mm
Lamp holder:	OTHER
Power:	12W
Gradations:	3000K
Light emission:	Direct
Nominal direct light beam:	1234 lm
Beam angle:	40°
CRI:	>90
Dimmer:	DALI
Power supply :	220-240V
Protection degree:	IP20
Insulation class:	II

In order to ensure a constant updating of its products, ROSSINI ILLUMINAZIONE reserves the right to make changes to improve without notice.



MAAR MAA101NDA



Rossiniilluminazione.