



AVERY





Apparecchio LED a parete per esterno (IP65), monoemissione e biemissione, tondo o quadrato.

Struttura in pressofusione di alluminio e diffusore in vetro temperato. Disponibile in tre finiture (antracite, grigio e marrone) e in due temperature colore (3000K e 4000K).

Disponibili giunti certificati IP68 per la realizzazione delle connessioni elettriche, sicure, durevoli e con barriera anticondensa.

Outdoor (IP65) wall LED luminaire with direct or direct/indirect light emission, with round or square shape.

Die-cast aluminium body and tempered glass diffuser. Available in three finishes (anthracite, grey and brown) and in two gradations (3000K and 4000K).

IP68 linear connectors for moisture protection and anti-condensation linear joints are available.



AVERY

MONOEMISSIONE DIRECT LIGHT



LED ▲ 40° CRI≥80 IP65

Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
AVE007XX	3000K	2520	15,6W	Ø130 x 250 x 190
AVE008XX	4000K	2620	15,6W	Ø130 x 250 x 190





BIEMISSIONE DIRECT-INDIRECT LIGHT



LED ▲ 40° CRI≥80 IP65

Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
AVE005XX	3000K	2520+2520	2x15,6W	Ø130 x 250 x 190
AVE006XX	4000K	2620+2620	2x15,6W	Ø130 x 250 x 190





MONOEMISSIONE DIRECT LIGHT



LED ▲ 40° CRI≥80 IP65

Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
AVE003XX	3000K	2520	15,6W	130 x 220 x 200
AVE004XX	4000K	2620	15,6W	130 x 220 x 200





BIEMISSIONE DIRECT-INDIRECT LIGHT



LED ▲ 40° CRI≥80 IP65

Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
AVE001XX	3000K	2520+2520	2x15,6W	130 x 220 x 200
AVE002XX	4000K	2620+2620	2x15,6W	130 x 220 x 200




Finiture Finishes



GR



AN



MA

Accessori Accessories



connessione IP68
IP68 connection

p.897