





# LEO



New





# LEO

Paletto LED da terra per esterno (IP65) con alimentatore integrato. Struttura in pressofusione di alluminio con polveri poliestere ad elevata resistenza ai raggi ultravioletti e alla corrosione e diffusore in policarbonato. Disponibile in due altezze, in due finiture (grigio e antracite), due temperature colore (3000K e 4000K).

Grazie al suo design emette luce diffusa e confortevole verso il basso, proprio dove serve, illuminando giardini, verande, viali ed ingressi. Disponibili giunti certificati IP68 per la realizzazione di connessioni elettriche sicure, con barriera anticondensa.

Outdoor (IP65) LED bollard with integrated LED driver. Die-cast aluminum painted with polyester powders body with high resistance to UV rays and corrosion and polycarbonate diffuser. Available in two heights, two finishes (grey and anthracite), two gradations (3000K and 4000K).

Thanks to its design it emits diffused and comfortable light downwards, right where it is needed, illuminating gardens, verandas, avenues and entrances. IP68 linear connectors for moisture protection and anti-condensation linear joints are available.



New











Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
<b>LEO001XX</b>	3000K	2880	25W	Ø180 x 45 x 660
<b>LEO002XX</b>	4000K	3020	25W	Ø180 x 45 x 660
<b>LEO003XX</b>	3000K	2880	25W	Ø180 x 45 x 1060
<b>LEO004XX</b>	4000K	3020	25W	Ø180 x 45 x 1060



## Finiture Finishes



## Accessori Accessories



connessione IP68  
IP68 connection

p.897