



Poliedrico.
Multi-faceted.

SILVER



Apparecchio LED a parete per esterno (IP65) monoemissione e biemissione. Struttura in pressofusione di alluminio verniciato con polveri poliestere a elevata resistenza ai raggi ultravioletti e alla corrosione, diffusore in vetro temperato. Guarnizioni in silicone e viti di chiusura in acciaio INOX.

Disponibile in forma quadrata e stondata, in tre finiture (grigio, antracite e marrone) e in due temperature colore (3000K e 4000K).

Disponibili giunti certificati IP68 per la realizzazione delle connessioni elettriche, sicure, durevoli e con barriera anticorrosione.

Outdoor (IP65) wall LED luminaire with direct or direct/indirect light emission. Die-cast aluminium body painted with polyester powders, highly resistant to UV rays and corrosion, tempered glass diffuser.

Silicone gasket and INOX steel screws. Available in round and square shape, in three finishes (grey, anthracite and brown) and in two gradations (3000K and 4000K).

IP68 linear connectors for moisture protection and anti-condensation linear joints are available.





SILVER

MONOEMISSIONE DIRECT LIGHT



LED ▲ 60° CRI≥80 IP65

Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
A.122-XX-LED-C	3000K	420	1x4,5W	100 x 100 x 110
A.122-XX-LED-F	4000K	505	1x4,5W	100 x 100 x 110





BIEMISSIONE DIRECT-INDIRECT LIGHT



LED ▲ 60° CRI≥80 IP65

Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
A.124-XX-LED-C	3000K	420+420	2x4,5W	100 x 100 x 110
A.124-XX-LED-F	4000K	505+505	2x4,5W	100 x 100 x 110





MONOEMISSIONE DIRECT LIGHT



LED ▲ 60° CRI≥80 IP65

Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
A.129-XX-LED-C	3000K	420	1x4,5W	96 x 96 x 112
A.129-XX-LED-F	4000K	505	1x4,5W	96 x 96 x 112





BIEMISSIONE DIRECT-INDIRECT LIGHT



LED ▲ 60° CRI≥80 IP65

Codice Code	CCT	Flusso lm Flux lm	Potenza Wattage	Dimensioni mm Dimensions mm
A.130-XX-LED-C	3000K	420+420	2x4,5W	96 x 96 x 112
A.130-XX-LED-F	4000K	505+505	2x4,5W	96 x 96 x 112



Finiture Finishes



GR



AN



MA

Accessori Accessories



connessione IP68
IP68 connection

p.897